

MF2600 Series

HP/kW
65-75/48-55



The MF 2600 is the ideal multi-purpose tractor for your farm, handling every task that you set for it. Perfect for arable farms with its powerful three or four-cylinder engine and flexible transmission choices, the MF 2600 is also a highly suitable workhorse for livestock and dairy farmers and growers of fruit and vegetables, vines and olives.

Standard cab and non-cab versions are designed for open field agricultural applications, and are capable of handling a wide range of implements from cultivation and seeding equipment to hay and forage tools.

Non-cab, open platform versions make for easy access where operators need to get on and off the tractor frequently, for example when harvesting vegetables or feeding livestock. Massey Ferguson's renowned cabs give the ultimate in comfort and protection from the elements, while offering plenty of space and easy access.

There's a model and specification that's exactly right for your farm.

SPECIFICATIONS

Engine	MF 2630	MF 2630 F	MF 2635
Max (ISO 14396) hp	65	65	75
Engine rpm @ max power	2200	2200	2200
Engine type / Emission level	Simpson SJ 436 E / Stage III A		
No of cylinders / Aspiration / Capacity (cc)	4 / Turbo / 3600		
Clutch			
Type with live PTO	Dry Dual Disc		
Type with independent PTO	Dry Single Disc		
Hydraulic engaged independent PTO clutch	Wet Multi Disc		
Steering type	Hydrostatic		
Transmission			
Standard transmission, max speed	12F x 4R		
Brakes & final reduction			
4WD Front Axle	Optional		
12F/4R	Reduced Transmission		
Brakes	Mechanical actuated, wet discs		
Differential Lock	Mechanical actuated		
Power Take-off (Rear)			
Mechanical Clutch (PTO)	Standard		
Synchro (PTO)	Optional		
PTO	Optional		
Engine rpm @ 540 PTO Speed	1790		
PTO Power (hp) @ rated speed (rpm)	61@2200	61@2200	66@2200
Linkage & Hydraulics			
Pump model & type	Scotch Yoke Pump, Leveling control, Position control		
Max oil flow (l/min)	18		
Max Pressure (bar)	200		
Max Lift Capacity (kg)	2500		
External Hydraulic Pump Flow (l/min)	42		
Spool Valves	1 Standard / 2 Optional		
Fuel tank (litres)	65	65	85
Wheels and Tyres			
Rear Tyres 2WD/4WD	16,9 - 30	14,9 - 28 - 12.4x36	18,4 - 30 / 13,6 - 36
Front Tyres 2WD/4WD	7.5 x 16 / 9.5 - 24	7.5 x 16 - 300 / 70R20 - 9,5 - 24	7.5 x 16 / 12.4-24 / 11.2 - 24
Weights and Dimensions			
Wheelbase (mm) 2WD/4WD	2080/2090	2080/2090	2235/2245
Length (mm) 2WD/4WD	3970	3970	4081/4100
Width (mm)	2070	1745	2083/2109
Min Track width (mm)	2WD 1320F - 1400R	1321F - 1359R	1442F - 1626R
	4WD 1400F - 1400R	1336F - Arka R	1502F - 1626R
Height (from rollbar) (mm)	2430	2385	2469 - 2750 (over cab)
Ground clearance (mm)	320	275	320
Weight (kg) 2WD/4WD	3022 / 3227	2900 / 3130	3210 / 3500